

Number: UK9-53

## UK DECLARATION OF PERFORMANCE

In compliance with the Construction Products Regulation (EU) No 305/2011  
as amended by The Construction Products (Amendment etc.)  
(EU Exit) Regulations 2019 (S.I. 2019/465)

- 1 Unique identification code of the product-type:

**COLPOR 200PF, 1138100, 1138140**

- 2 Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:

**Joint sealants for concrete pavements - cold applied**

- 3 Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



**Fosroc International Limited**  
Drayton Manor Business Park  
Coleshill Road, Tamworth  
Staffordshire, B78 3XN, UK

- 4 Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

**Not Relevant**

- 5 System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

**System 4**

- 6a In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

**EN 14188-2:2004**

The notified body

**The product is subject to in-plant production control**

- 6b In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

**Not Relevant**

Issue Number: 1

Number: UK9-53

7 Declared performance

| Essential Characteristics                                 | Performance                              | Test Method |
|-----------------------------------------------------------|------------------------------------------|-------------|
| Bonding strength                                          | 23°C ≥ 0.15 MPa<br>-20°C ≤ 0.6 MPa       | EN 28340    |
| Cohesion for cold climate areas                           | No failure at -30°C ≤ 1.0MPa             | EN 14187-9  |
| Elastic recovery                                          | ≥70%                                     | EN ISO 7389 |
| Adhesion/cohesion properties after immersion in liquid    | No failure                               | EN 14187-6  |
| Change in mass/volume after immersion in liquid chemicals | Change in mass ≤-25% and ≤+30% by volume | EN 14187-4  |
| Artificial weathering by UV irradiation                   | ≤20% change in modulus at 100% extension | EN 14187-8  |
| Resistance to flame                                       | Pass                                     | EN 14187-7  |

8 Appropriate Technical Documentation and/or Specific Technical Documentation:

**Not Relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for the manufacturer and in the name of the manufacturer by:

Jon Potter  
Technical Manager



Place and Date of Issue: 30th June 2022 Tamworth

Issue Number: 1