

FRAGMAT NEO SUPER F

Description of the product: Cut board of expanded polystyrene (EPS)

Characteristics of the product: Boards Fragmat NEO SUPER F are with grey - black colour, without aroma and it doesn't consist any harmful ingredients. The boards are in rectangular form 0.5m x 1.0m, with Thickness 6cm (60mm).

The quality responds to standard EN 13163, and reaction to fire responds to DIN 4103 in class B1, or by EN 13501-1 in class E. It doesn't consists Freon (CFC free).

Code index by EN 13163:

EPS-EN 13163-T2-L2-W2-S1-P5-BS150-CS(10)90-WL(T)2-MU-DS(70,-)1-TR190

Characteristic	EN Method	Unit	Declaration	Tolerance
Length	822	mm	L2	± 2
Width	822	mm	W2	± 2
Thickness	823	mm	T2	± 1
Squareness 1000 mm	824	mm	S1	± 5
Flatness	825	mm	P5	± 3
Bending strength	12089	kPa	BS182	≥ 100
Tensile strength	1607	kPa	194	≥ 100
	DIN 1408-10	kPa	194	≥ 100
Dimensional stability	1604	%	DS(70,-)	± 1.0
Reaction to fire	EN 13501-1		class E	
Thermal resistance (λ_D)	12667	W/m.K	0.0302	
Compressive strength (at 10% deformation)	EN 826	kPa	92	≥ 90

Tested thickness

Thickness (mm)	60
Thermal resistance – RD [m ² K/W]	1.98

Intended use: Boards Fragmat NEO SUPER F are in use for thermal insulation, to protect the object in according to ETAG 004.

Method of building: Most suitable way is with sticking and mechanic attachment. While the construction process it should not be a subject of direct sunbeam (compulsorily use of protecting nets)

Storing; Packing The packing are in packages, which consist 0.24 m³ per package, with PE foil. The packing is taking at closed room, protected from UV ray, warmth, flame and other chemicals which can damage the product.

Certification body: NIISM, SOFIA, Ilija Beshkov 1
Accredited by IA "BSA"
Certificate no. 47 – approved N CPD 05-NB 1950/17/09

