



## SAFETY DATA SHEET NITOCOTE CM210 LIQUID

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** NITOCOTE CM210 LIQUID  
**Product number** A1737003UK9

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Polymeric additive for cementitious products.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** FOSROC Limited  
 Drayton Manor Business Park  
 Coleshill Road  
 Tamworth  
 Staffordshire  
 B78 3XN  
 enquiryuk@fosroc.com  
 Tel. +44 (0) 1827 262222  
 Fax. +44 (0) 1827 262444

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards** Not Classified  
**Health hazards** Not Classified  
**Environmental hazards** Not Classified

**Human health** See Section 11 for additional information on health hazards.

**Environmental** The product is not expected to be hazardous to the environment.

#### 2.2. Label elements

**Hazard statements** NC Not Classified

#### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## NITOCOTE CM210 LIQUID

**Composition comments** This product contain a substance at a concentration of  $\geq 0.1$  % w/w which is included in the candidate list according to Article 59 (1, 10) of REACH Regulation EC No. 1907/2006:;4-1,1,3,3,-tetramethylbutyl)phenol, ethoxylated (CAS No. 9002-93-1)„Content w/w <0.15%.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**General information** No specific recommendations. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation.

**Ingestion** Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

**Skin contact** Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

**Eye contact** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** No specific symptoms noted.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** The product is non-combustible. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Material can splatter above 100°C. Polymer film can burn. Irritant fumes.

**Hazardous combustion products** Does not decompose when used and stored as recommended.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Move containers from fire area if it can be done without risk. No specific firefighting precautions known. Control run-off water by containing and keeping it out of sewers and watercourses.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** For personal protection, see Section 8.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. For waste disposal, see Section 13.

## NITOCOTE CM210 LIQUID

### 6.4. Reference to other sections

**Reference to other sections** For waste disposal, see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Good personal hygiene procedures should be implemented.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store at temperatures above °C/°F.

**Storage class** Chemical storage.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

**Ingredient comments** No exposure limits known for ingredient(s).

#### 8.2. Exposure controls

##### Protective equipment



**Appropriate engineering controls** Provide adequate general and local exhaust ventilation.

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

**Hand protection** Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Nitrile rubber. Neoprene.

**Other skin and body protection** Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.

**Hygiene measures** Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**Respiratory protection** No specific recommendations.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

**Appearance** Liquid.

**Colour** White.

**Odour** Acrylic

**Odour threshold** Not determined.

**pH** pH (concentrated solution): 7.0 - 9.0

## NITOCOTE CM210 LIQUID

<b>Melting point</b>	0°C
<b>Initial boiling point and range</b>	100°C @ 101 kPa
<b>Flash point</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	The product is not flammable.
<b>Other flammability</b>	Not applicable.
<b>Vapour pressure</b>	2.3 kPa @ 20°C
<b>Vapour density</b>	Not determined.
<b>Relative density</b>	1.05 @ 20°C
<b>Bulk density</b>	Not applicable.
<b>Solubility(ies)</b>	Emulsible in water.
<b>Auto-ignition temperature</b>	Not applicable.
<b>Explosive properties</b>	Not considered to be explosive.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

### 9.2. Other information

**Other information** Not available.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** After long storage, very small quantities of carbon monoxide may be formed.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid excessive heat for prolonged periods of time. Avoid freezing.

### 10.5. Incompatible materials

**Materials to avoid** No specific material or group of materials is likely to react with the product to produce a hazardous situation.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

## NITOCOTE CM210 LIQUID

**Toxicological effects** This product has low toxicity.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure

**General information** No specific health hazards known.

**Skin contact** Prolonged and frequent contact may cause redness and irritation. Not a skin sensitiser.

**Medical symptoms** No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

## SECTION 12: Ecological Information

**Ecotoxicity** The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** Not expected to be ecotoxic to fish/daphnia/algae

### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** The product is miscible with water. May spread in water systems.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** Not applicable.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be considered.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Waste liquid components should be suitable for incineration at an approved facility.

## SECTION 14: Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

## NITOCOTE CM210 LIQUID

### 14.3. Transport hazard class(es)

No transport warning sign required.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

#### **Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>Revision comments</b>	NOTE: Lines within the margin indicate significant changes from the previous revision.
<b>Revision date</b>	16/07/2015
<b>Revision</b>	3
<b>Risk phrases in full</b>	NC Not classified. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



## SAFETY DATA SHEET NITOCOTE CM210 GREY

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** NITOCOTE CM210 GREY

**Product number** A1737108UK9

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cementitious overlay

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** FOSROC Limited  
 Drayton Manor Business Park  
 Coleshill Road  
 Tamworth  
 Staffordshire  
 B78 3XN  
 enquiryuk@fosroc.com  
 Tel. +44 (0) 1827 262222  
 Fax. +44 (0) 1827 262444

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** Xi;R37/38,R41. R43.

**Human health** Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

**Environmental** The product will harden into a solid mass in contact with water and moisture. The resultant material is not biodegradable.

#### 2.2. Label elements

## NITOCOTE CM210 GREY

### Pictogram



### Signal word

Danger

### Hazard statements

H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.  
 H315 Causes skin irritation.

### Precautionary statements

P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P501 Dispose of contents/container in accordance with national regulations.

### Contains

ORDINARY PORTLAND CEMENT

### Supplementary precautionary statements

P261 Avoid breathing vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P310 Immediately call a POISON CENTER/doctor.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>ORDINARY PORTLAND CEMENT</b>	<b>30-60%</b>
CAS number: 65997-15-1	EC number: 266-043-4
<b>Classification</b> Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335	



## NITOCOTE CM210 GREY

<b>FORMALDEHYDE</b>	<b>&lt;1%</b>
CAS number: 50-00-0	EC number: 200-001-8
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Acute Tox. 4 - H302	Carc. Cat. 3;R40 T;R23/24/25 C;R34 R43
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
Skin Corr. 1B - H314	
Skin Sens. 1 - H317	
Carc. 2 - H351	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet cement or wet cement containing preparations.
<b>Inhalation</b>	Move affected person to fresh air at once. Dust in throat and nasal passages should clear spontaneously. Get medical attention if irritation persists or later develops, or if discomfort, coughing or other symptoms persist.
<b>Ingestion</b>	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention immediately.
<b>Skin contact</b>	Wash immediately with copious quantities of water. Remove contaminated clothing immediately. Obtain medical advice if skin orders develop.
<b>Eye contact</b>	Do not rub eye. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for 30 minutes. Get medical attention. Show this Safety Data Sheet to the medical personnel.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
<b>Ingestion</b>	Ingestion of large doses may result in irritation to the gastrointestinal tract.
<b>Skin contact</b>	May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis after repeated contact. Prolonged skin contact with wet preparation may cause serious burns without pain being felt, including through clothing.
<b>Eye contact</b>	Eye contact may cause serious and potentially irreversible injuries.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

## NITOCOTE CM210 GREY

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted.

**Hazardous combustion products** No known hazardous decomposition products.

### 5.3. Advice for firefighters

**Protective actions during firefighting** No specific firefighting precautions known.

**Special protective equipment for firefighters** Use protective equipment appropriate for surrounding materials.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid inhalation of dust. Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Dry material: Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. The product contains less than 2 mg chromate/kg dry cement, and this limit will not be exceeded for 12 months from the packing date stated on the packaging. Seal opened containers and use up as soon as possible. To be stored out of reach of children in its original packaging in a dry place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

## NITOCOTE CM210 GREY

### Occupational exposure limits

#### SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m<sup>3</sup>

#### ORDINARY PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

#### FORMALDEHYDE

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2,5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 2 ppm 2,5 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

#### ORDINARY PORTLAND CEMENT (CAS: 65997-15-1)

##### DNEL

Workers - Inhalation; Short term : 3 mg/m<sup>3</sup>

#### FORMALDEHYDE (CAS: 50-00-0)

##### DNEL

Workers - Inhalation; Long term systemic effects: 9 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

#### Personal protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. It contains a chromate reducing agent, but users should wear appropriate personal protective equipment.

#### Eye/face protection

The following protection should be worn: Chemical splash goggles. (conform EN 166)

#### Hand protection

Use impervious, abrasion and alkali resistant gloves. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

#### Other skin and body protection

Use barrier creams to prevent skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.

#### Hygiene measures

This product contains silica sands.  
The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may cause health effects.  
Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness.  
Occupational exposure to respirable crystalline silica dust should be monitored and controlled

#### Respiratory protection

Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

### SECTION 9: Physical and Chemical Properties

## NITOCOTE CM210 GREY

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Dusty powder.
<b>Colour</b>	Grey.
<b>Odour</b>	Odourless.
<b>Odour threshold</b>	Not relevant.
<b>pH</b>	pH (diluted solution): > 12
<b>Melting point</b>	>1250°C
<b>Initial boiling point and range</b>	Not applicable.
<b>Flash point</b>	Not applicable.
<b>Evaporation rate</b>	Not applicable.
<b>Evaporation factor</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	The product is not flammable.
<b>Vapour pressure</b>	Not applicable.
<b>Vapour density</b>	Not applicable.
<b>Relative density</b>	1.30 (bulk) @ 20°C
<b>Solubility(ies)</b>	Insoluble in water.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	Not applicable.
<b>Explosive properties</b>	Not considered to be explosive.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
<b>Comments</b>	Information given is applicable to the product as supplied.

### 9.2. Other information

**Other information** Not available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.

### 10.2. Chemical stability

## NITOCOTE CM210 GREY

**Stability** Stable under the prescribed storage conditions. When stored under humid conditions, the chromate neutralization will decrease. This product contains a chromate reducing agent to reduce the risk of allergic dermatitis caused by chromium (VI). This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry), there is an increased risk of the presence of hexavalent chromate leading to an increased risk of an allergic reaction.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not known. Will not polymerise.

### 10.4. Conditions to avoid

**Conditions to avoid** Water, moisture.

### 10.5. Incompatible materials

**Materials to avoid** Acids Chemically-active metals.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Skin sensitisation

**Skin sensitisation** Some individuals may exhibit eczema upon exposure to wet cement caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness is not exceeded, a sensitising effect is not expected.

#### **Inhalation**

Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.

#### **Ingestion**

May cause irritation of mouth, throat and digestive tract.

#### **Skin contact**

This product is strongly irritating. Prolonged contact may cause burns. May cause sensitisation by skin contact.

#### **Eye contact**

Irritating and may injure eye tissue if not removed promptly.

#### **Acute and chronic health hazards**

Repeated and/or prolonged contact may lead to dermatitis

## SECTION 12: Ecological Information

#### **Ecotoxicity**

The product is not expected to be hazardous to the environment.

### 12.1. Toxicity

#### **Acute toxicity - fish**

The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.

### 12.2. Persistence and degradability

**Persistence and degradability** The product is not biodegradable.

### 12.3. Bioaccumulative potential

## NITOCOTE CM210 GREY

**Bioaccumulative potential**      The product is not bioaccumulating.

### 12.4. Mobility in soil

**Mobility**      The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment**      This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects**      None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information**      Do not empty into drains, sewers or water courses. Cement that has exceeded its shelf life: when demonstrated that it contains more than 0.0002% Cr (VI), the product shall not be used other than in controlled closed and totally automated processes. It may be recycled and/or treated again with a reducing agent.

**Disposal methods**      Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Note that fully cured material is not considered as hazardous waste.

## SECTION 14: Transport information

**General**      The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

Not applicable.

**UN No. (IMDG)**

**UN No. (ICAO)**

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

Not relevant.

**ADR/RID class**

**ADR/RID subsidiary risk**

**ADR/RID label**

**IMDG class**

**IMDG subsidiary risk**

**ICAO class/division**

**ICAO subsidiary risk**

**Transport labels**

### 14.4. Packing group

## NITOCOTE CM210 GREY

Not applicable.

**ADR/RID packing group**

**IMDG packing group**

**ICAO packing group**

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

Not applicable.

**EmS**

**Emergency Action Code**

**Hazard Identification Number  
(ADR/RID)**

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

**Transport in bulk according to** Not applicable.

**Annex II of MARPOL 73/78  
and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>General information</b>	Only trained personnel should use this material.
<b>Revision comments</b>	NOTE: Lines within the margin indicate significant changes from the previous revision.
<b>Revision date</b>	22/07/2015
<b>Revision</b>	3
<b>Risk phrases in full</b>	R23/24/25 Toxic by inhalation, in contact with skin and if swallowed. R34 Causes burns. R37 Irritating to respiratory system. R37/38 Irritating to respiratory system and skin. R40 Limited evidence of a carcinogenic effect. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact.

## NITOCOTE CM210 GREY

### **Hazard statements in full**

H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.





## SAFETY DATA SHEET NITOCOTE CM210 WHITE

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** NITOCOTE CM210 WHITE

**Product number** A1737542UK9

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cementitious overlay

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** FOSROC Limited  
 Drayton Manor Business Park  
 Coleshill Road  
 Tamworth  
 Staffordshire  
 B78 3XN  
 enquiryuk@fosroc.com  
 Tel. +44 (0) 1827 262222  
 Fax. +44 (0) 1827 262444

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** -

**Human health** Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.

**Environmental** The product will harden into a solid mass in contact with water and moisture. The resultant material is not biodegradable.

#### 2.2. Label elements

## NITOCOTE CM210 WHITE

### Pictogram



### Signal word

Danger

### Hazard statements

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.

### Precautionary statements

P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P501 Dispose of contents/container in accordance with national regulations.

### Contains

CEMENT

### Supplementary precautionary statements

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe vapour/spray.  
 P261 Avoid breathing vapour/spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P310 Immediately call a POISON CENTER/doctor.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P314 Get medical advice/attention if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>SILICA SAND</b>	<b>60-100%</b>
CAS number: 14808-60-7	EC number: 238-878-4
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Not Classified	-



## NITOCOTE CM210 WHITE

<b>Skin contact</b>	May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis after repeated contact. Prolonged skin contact with wet preparation may cause serious burns without pain being felt, including through clothing.
<b>Eye contact</b>	Eye contact may cause serious and potentially irreversible injuries.

### **4.3. Indication of any immediate medical attention and special treatment needed**

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

## SECTION 5: Firefighting measures

### **5.1. Extinguishing media**

<b>Suitable extinguishing media</b>	The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.
-------------------------------------	---

### **5.2. Special hazards arising from the substance or mixture**

<b>Specific hazards</b>	Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted.
-------------------------	--

<b>Hazardous combustion products</b>	No known hazardous decomposition products.
--------------------------------------	--

### **5.3. Advice for firefighters**

<b>Protective actions during firefighting</b>	No specific firefighting precautions known.
---	---

<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
--	---

## SECTION 6: Accidental release measures

### **6.1. Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Avoid inhalation of dust. Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	--

### **6.2. Environmental precautions**

<b>Environmental precautions</b>	Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

### **6.3. Methods and material for containment and cleaning up**

<b>Methods for cleaning up</b>	Dry material: Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.
--------------------------------	---

### **6.4. Reference to other sections**

<b>Reference to other sections</b>	For personal protection, see Section 8. For waste disposal, see section 13.
------------------------------------	---

## SECTION 7: Handling and storage

### **7.1. Precautions for safe handling**

<b>Usage precautions</b>	Avoid generation and spreading of dust. Do not eat, drink or smoke when using the product. Avoid inhalation of dust. Avoid contact with skin and eyes. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing.
--------------------------	---

## NITOCOTE CM210 WHITE

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. Seal opened containers and use up as soon as possible To be stored out of reach of children in its original packaging in a dry place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m<sup>3</sup>

##### CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup>

##### FORMALDEHYDE ...%

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2,5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 2 ppm 2,5 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

#### FORMALDEHYDE ...% (CAS: 50-00-0)

##### DNEL

Workers - Inhalation; Long term systemic effects: 9 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

#### Personal protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

#### Eye/face protection

The following protection should be worn: Chemical splash goggles. (conform EN 166)

#### Hand protection

Use impervious, abrasion and alkali resistant gloves. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

#### Other skin and body protection

Use barrier creams to prevent skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.

## NITOCOTE CM210 WHITE

<b>Hygiene measures</b>	<p>This product contains silica sands.</p> <p>The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may may cause health effects.</p> <p>Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness.</p> <p>Occupational exposure to respirable crystalline silica dust should be monitored and controlled</p>
<b>Respiratory protection</b>	Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Dusty powder.
<b>Colour</b>	White
<b>Odour</b>	Odourless.
<b>pH</b>	pH (concentrated solution): >12
<b>Melting point</b>	>1250°C
<b>Initial boiling point and range</b>	Not applicable.
<b>Solubility(ies)</b>	Slightly soluble in water. Hardens in contact with water.

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.
-------------------	---

#### 10.2. Chemical stability

<b>Stability</b>	Dry cements are stable as long as they are stored properly (see section 7). When mixed with water, cements will harden into a stable mass that is not reactive to normal environments.
------------------	--

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Not known. Will not polymerise.
---	---------------------------------

#### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Water, moisture.
----------------------------	------------------

#### 10.5. Incompatible materials

<b>Materials to avoid</b>	Acids Chemically-active metals.
---------------------------	---------------------------------

#### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	No known hazardous decomposition products.
---	--

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Skin sensitisation

## NITOCOTE CM210 WHITE

<b>Skin sensitisation</b>	Some individuals may exhibit eczma upon exposure to wet cement caused by the high pH which induces irritant contact dermatitis.
<b>Inhalation</b>	Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.
<b>Ingestion</b>	May cause irritation of mouth, throat and digestive tract.
<b>Skin contact</b>	This product is strongly irritating. Prolonged contact may cause burns.
<b>Eye contact</b>	Irritating and may injure eye tissue if not removed promptly.
<b>Acute and chronic health hazards</b>	Repeated and/or prolonged contact may lead to dermatitis

### SECTION 12: Ecological Information

**Ecotoxicity** The product is not expected to be hazardous to the environment.

#### 12.1. Toxicity

**Acute toxicity - fish** Not determined.  
The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.

#### 12.2. Persistence and degradability

**Persistence and degradability** The product is not biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** The product is not bioaccumulating.

#### 12.4. Mobility in soil

**Mobility** The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### 12.6. Other adverse effects

**Other adverse effects** Not relevant.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Do not empty into drains, sewers or water courses.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Note that fully cured material is not considered as hazardous waste.

### SECTION 14: Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

## NITOCOTE CM210 WHITE

Not relevant.

### 14.2. UN proper shipping name

Not relevant.

### 14.3. Transport hazard class(es)

Not relevant.

### 14.4. Packing group

Not relevant.

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

Not relevant.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not relevant.

**Annex II of MARPOL 73/78  
and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>General information</b>	Only trained personnel should use this material.
<b>Revision comments</b>	NOTE: Lines within the margin indicate significant changes from the previous revision.
<b>Revision date</b>	28/05/2015
<b>Revision</b>	3



## NITOCOTE CM210 WHITE

### Hazard statements in full

H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H331 Toxic if inhaled.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.