

SAFETY DATA SHEET PAVEROC

SECTION 1: Identification of the	ne substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	PAVEROC
Product number	2065002UK9
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
Identified uses	Reinstatement Mortar
1.3. Details of the supplier of the	he safety data sheet
Supplier	FOSROC Limited Drayton Manor Business Park Coleshill Road Tamworth Staffordshire B78 3XN enquiryuk@fosroc.com Tel. +44 (0) 1827 262222 Fax. +44 (0) 1827 262444
1.4. Emergency telephone nur	nber
Emergency telephone	+44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 08.30 to 16.00hrs Fri)
SECTION 2: Hazards identification	ation
2.1. Classification of the subst	ance or mixture
Classification	Not Classified
Physical hazards Health hazards	
Environmental hazards	Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335 Not Classified
	Not Classifieu
Classification (67/548/EEC or 1999/45/EC)	Xi;R37/38,R41. R43.
Human health	Dust or splashes from the mixture may cause permanent eye damage. Dust may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Dust has an irritating effect on moist skin. Prolonged contact with moist or wet product may cause burns. Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
Environmental	The product will harden into a solid mass in contact with water and moisture. The resultant material is not biodegradable.

Pictogram



Signal word	Danger
Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.
Precautionary statements	 P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with national regulations.
Contains	ORDINARY PORTLAND CEMENT, CALCIUM SULPHO-ALUMINATE CEMENT
Supplementary precautionary statements	 P261 Avoid breathing vapour/spray. P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 Immediately call a POISON CENTER/doctor. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ORDINARY PORTLAND CEMENT		10-30%
CAS number: 65997-15-1	EC number: 266-043-4	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	Xi;R37/38,R41. R43.	
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
STOT SE 3 - H335		

GROUND GRANULATED BLASTFURNACI	E SLAG (GGBS)	1-5%
CAS number: 65996-69-2		
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	Xi;R36/38.	
Eye Irrit. 2 - H319 CALCIUM SULPHO-ALUMINATE CEMENT		1-5%
•		1-5%
CALCIUM SULPHO-ALUMINATE CEMENT	Classification (67/548/EEC or 1999/45/EC)	1-5%
CALCIUM SULPHO-ALUMINATE CEMENT CAS number: 12004-14-7		1-5%

SECTION 4: First aid measures 4.1. Description of first aid measures	
Inhalation	Move affected person to fresh air at once. Dust in throat and nasal passages should clear spontaneously. Get medical attention if irritation persists or later develops, or if discomfort, coughing or other symptoms persist.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Skin contact	Wash immediately with copious quantities of water. Remove contaminated clothing immediately. Obtain medical advice if skin orders develop.
Eye contact	Do not rub eye. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for 30 minutes. Get medical attention. Show this Safety Data Sheet to the medical personnel.
4.2. Most important symp	toms and effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
Ingestion	Ingestion of large doses may result in irritation to the gastrointestinal tract.
Skin contact	May have an irritating effect on moist skin after prolonged contact, or may cause dermatitis after repeated contact. Prolonged skin contact with wet preparation may cause serious burns without pain being felt, including through clothing.
Eye contact	Eye contact may cause serious and potentially irreversible injuries.
4.3. Indication of any imm	ediate medical attention and special treatment needed
Notes for the doctor	No specific recommendations.

SECTION 5: Firefighting measures 5.1. Extinguishing media Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. 5.2. Special hazards arising from the substance or mixture Specific hazards Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted. Hazardous combustion No known hazardous decomposition products. products 5.3. Advice for firefighters Protective actions during No specific firefighting precautions known. firefighting Special protective equipment Use protective equipment appropriate for surrounding materials. for firefighters SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures Personal precautions Avoid inhalation of dust. Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet. 6.2. Environmental precautions **Environmental precautions** Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground. 6.3. Methods and material for containment and cleaning up Methods for cleaning up Dry material: Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Collect powder using special dust vacuum cleaner with particle filter. Alternatively, damp powder with fine spray (to avoid dust formation) and remove slurry. Place into container and allow to solidify before disposal as described in section 13. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13. 6.4. Reference to other sections Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13. SECTION 7: Handling and storage 7.1. Precautions for safe handling Usage precautions Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product. 7.2. Conditions for safe storage, including any incompatibilities Storage precautions Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. The product contains less than 2 mg chromate/kg dry cement, and this limit will not be exceeded for 12 months from the packing date stated on the packaging. Seal opened containers and use up as soon as possible To be stored out of reach of children in its original packaging in a dry place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m³

GRANITE CHIPS

Long-term exposure limit (8-hour TWA): OES 10 mg/m³

ORDINARY PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

CALCIUM SULPHO-ALUMINATE CEMENT

Long-term exposure limit (8-hour TWA): TLV - Threshold Limit Value 10 mg/m³

WEL = Workplace Exposure Limit

ORDINARY PORTLAND CEMENT (CAS: 65997-15-1)

DNEL	Workers - Inhalation; Short term : 3 mg/m ³
	2,2-DIMETHYL 1,3-PROPANEDIOL (CAS: 126-30-7)
DNEL	Workers - Inhalation; Long term systemic effects: 35 mg/m ³ Workers - Dermal; Long term systemic effects: 10 mg/kg bw/day General population - Inhalation; Long term systemic effects: 8.7 mg/m ³ General population - Dermal; Long term systemic effects: 5 mg/kg bw/day General population - Oral; Long term systemic effects: 5 mg/kg bw/day
PNEC	- Fresh water; 5 mg/l - Marine water; 0.5 mg/l - STP; 20 mg/l
	BASIC COPPER CARBONATE (CAS: 12069-69-1)
PNEC	- Fresh water; 7.8 μg/l - Marine water; 5.2 μg/l

- STP; 230 µg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Personal protection

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. It contains a chromate reducing agent, but users should wear appropriate personal protective equipment.

Eye/face protection	The following protection should be worn: Chemical splash goggles. (conform EN 166)
Hand protection	Use impervious, abrasion and alkali resistant gloves. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.
Other skin and body protection	Use barrier creams to prevent skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	This product contains silica sands. The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may may cause health effects. Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness. Occupational exposure to respirable crystalline silica dust should be monitored and controlled
Respiratory protection	Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Dusty powder.
Colour	Grey.
Odour	Odourless.
Odour threshold	Not relevant.
рН	pH (concentrated solution): >12
Melting point	>1250°C
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Evaporation factor	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	The product is not flammable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	1.3 @ at 20°C
Solubility(ies)	Slightly soluble in water. Hardens in contact with water.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.

Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
Comments	Information given is applicable to the product as supplied.
9.2. Other information	
Other information	Not available.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.
10.2. Chemical stability	
Stability	When stored under humid conditions, the chromate neutralization will decrease. Stable under the prescribed storage conditions. This product contains a chromate reducing agent to reduce the risk of allergic dermatitis causes by chromium (VI). This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry), there is an increased risk of the presence of hexavalent chromate leading to an increased risk of an allergic reaction.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	Not known. Will not polymerise.
10.4. Conditions to avoid	
Conditions to avoid	Water, moisture.
10.5. Incompatible materials	
Materials to avoid	Acids Chemically-active metals.
10.6. Hazardous decomposition	on products
Hazardous decomposition products	No known hazardous decomposition products.
SECTION 11: Toxicological in	formation
11.1. Information on toxicolog	ical effects
Skin sensitisation	
Skin sensitisation	Some individuals may exhibit eczema upon exposure to wet cement caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness is not exceeded, a sensitising effect is not expected.
Inhalation	Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.
Ingestion	May cause irritation of mouth, throat and digestive tract.
Skin contact	This product is strongly irritating. Prolonged contact may cause burns. May cause sensitisation by skin contact.
Eye contact	Irritating and may injure eye tissue if not removed promptly.
Acute and chronic health hazards	Repeated and/or prolonged contact may lead to dermatitis

SECTION 12: Ecological Information	
Ecotoxicity	The product is not expected to be hazardous to the environment.
12.1. Toxicity	
Acute toxicity - fish	Not determined. The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.
12.2. Persistence and degrada	ability
Persistence and degradability	The product is not biodegradable.
12.3. Bioaccumulative potentia	al
Bioaccumulative potential	The product is not bioaccumulating.
12.4. Mobility in soil	
Mobility	The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.
12.5. Results of PBT and vPv	B assessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal consid	lerations
13.1. Waste treatment method	ds
General information	Do not empty into drains, sewers or water courses. Cement that has exceeded its shelf life: when demonstrated that it contains more than 0.0002% Cr (VI), the product shall not be used other than in controlled closed and totally automated processes. It may be recycled and/or treated again with a reducing agent.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Note that fully cured material is not considered as hazardous waste.
SECTION 14: Transport inform	nation
General	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
14.1. UN number	
Not relevant.	
14.2. UN proper shipping nam	1e
Not relevant.	
14.3. Transport hazard class(es)
Not relevant.	
14.4. Packing group	
Not relevant.	

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not relevant.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not relevant. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Only trained personnel should use this material.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	11/07/2015
Revision	3
SDS number	21660
Risk phrases in full	R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.