

**Number: UK9-53**

**DECLARATION OF PERFORMANCE**

In accordance with Annex III of Registration (EU) No. 305/2011

**(Construction Product Regulation)**

**For the product Colpor 200PF**

1. Unique identification code of the product-type:  
**Colpor 200PF**
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):  
**Batch Number: See product packaging**
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:  
**EN 14188-2: Joint sealants for concrete pavements - cold applied**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



**Fosroc Limited**  
**Drayton Manor Business Park**  
**Coleshill Road, Tamworth**  
**Staffordshire, B78 3TL, UK**

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):  
**Not Relevant**
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V  
**System 4**
7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard  
**The product is subject to in-plant production control**
8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued  
**Not Relevant**
9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Bonding strength	23°C ≥ 0.15MPa	EN 28340
Bonding strength	-20°C ≤ 0.6MPa	EN 28340
Cohesion for cold climate areas	-30°C ≤ 1.0 no failure	EN 14187-9
Elastic recovery	≥70%	EN ISO 7389
Adhesion/cohesion properties after immersion in liquid chemicals	No failure	EN 14187-6
Change in mass/volume after immersion in liquid chemicals	Change in mass ≤-25% by mass and ≤30% by volume	EN 14187-4

## Number: UK9-53

Artificial weathering by UV irradiation	≤20% change in modulus at 100% extension	EN 14187-8
Resistance to flame	Pass/fail	EN 14187-7

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

### Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:

A handwritten signature in black ink that reads "Jeremy Bell".

Jeremy Bell,  
Technical Quality Manager

Place and Date of Issue:            03/12/2013            Tamworth