

Number: UK9-34

DECLARATION OF PERFORMANCE

In accordance with Annex III of Registration (EU) No. 305/2011

(Construction Product Regulation)

For the product Renderoc DS

1. Unique identification code of the product-type:
EN 1504-1 Polymer hydraulic cement mortars and concreted (PCC)
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4):
Batch Number: See product packaging
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification:
EN1504-3: Structural and non structural repair methods 3 and 4
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in article 11 (5)



Fosroc Limited
Drayton Manor Business Park
Colehill Road, Tamworth
Staffordshire, B78 3TL, UK

5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2):

Not Relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

System 2+

7. In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard

The notified body APPlus, identification number 0370, has carried out initial inspection of the factory and factory production control as well as continuous surveillance, assessment and evaluation of factory production control according to system 2+ and issued the following:

Certificate of Factory Production Control

No. 0370-CPD-0845

8. In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

Not Relevant

9. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Compressive strength	Class R4 (> 45 MPa)	EN 12190:1999
Chloride ion content	< 0.05 %	EN 1015-17:2000
Adhesion strength by pull-off test	≥ 2.0 MPa	EN 1542:2000
Thermal compatibility: freeze-	≥ 2.0 MPa	EN 13687-1

Number: UK9-34

thaw cycling with immersion


Carbonation resistance	Passes	EN 13295:2005
Elastic modulus	28.6 GPa	EN 13412:2002
Reaction to fire	Class A1	EN 13501-1
Dangerous substances	Complies with 5.4	
Capillary absorption (water permeability)	$\leq 0.5 \text{ kg m}^{-2} \text{ h}^{-0.5}$	EN 13057

When specified technical documentation in accordance with Articles 37 or 38 was used, the requirements that the product fulfils:

Not applicable

The performance of the product set out in numbers 1 and 2 corresponds to the declared performance set out in number 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and in the name of the manufacturer by:



Jeremy Bell,
Technical Quality Manager

Place and Date of Issue: 23/07/2013 Tamworth