



## SAFETY DATA SHEET

### Patchroc 250

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Patchroc 250

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Cementitious overlay

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** FOSROC Limited  
 Drayton Manor Business Park  
 Coleshill Road  
 Tamworth  
 Staffordshire  
 B78 3XN  
 Tel. +44 (0) 1827 262222  
 Fax. +44 (0) 1827 262444  
 enquiryuk@fosroc.com

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0) 1827 265 279 (08.30 to 17.00hrs Mon - Thu; 0.8.30 to 16.00hrs Fri)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Not Classified

**Health hazards** Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

**Environmental hazards** Not Classified

##### 2.2. Label elements

###### Pictogram



**Signal word** Danger

**Hazard statements** H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.

## Patchroc 250

<b>Precautionary statements</b>	P261 Avoid breathing dust.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P302+P352 IF ON SKIN: Wash with plenty of water.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P501 Dispose of contents/ container in accordance with national regulations.

**Contains** CEMENT POWDER, CALCIUM SULFOALUMINATE

<b>Supplementary precautionary statements</b>	P264 Wash contaminated skin thoroughly after handling.
	P310 Immediately call a POISON CENTER/ doctor.
	P321 Specific treatment (see medical advice on this label).
	P332+P313 If skin irritation occurs: Get medical advice/ attention.
	P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
	P362+P364 Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>CEMENT POWDER</b>	<b>10-30%</b>
CAS number: 65997-15-1	EC number: 266-043-4
<b>Classification</b>	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
STOT SE 3 - H335	
<b>SILICA SAND</b>	<b>50-70%</b>
CAS number: 14808-60-7	EC number: 238-878-4
<b>Classification</b>	
Not Classified	
<b>Calcium Carbonate - Limestone (13 Micron)</b>	<b>5-10%</b>
CAS number: 471-34-1	EC number: 207-439-9
<b>Classification</b>	
Not Classified	
<b>CALCIUM SULFOALUMINATE</b>	<b>5-10%</b>
CAS number: 12004-14-7	
<b>Classification</b>	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	

## Patchroc 250

<b>CALCIUM CARBONATE</b>	<b>1-5%</b>
CAS number: 1317-65-3	
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>CALCIUM SULPHATE B-ANHYDRITE</b>	<b>1-5%</b>
CAS number: 7778-18-9	
<b>Classification</b> Not Classified	<b>Classification (67/548/EEC or 1999/45/EC)</b> -
<b>TARTARIC ACID POWDER</b>	<b>&lt;1%</b>
CAS number: 87-69-4	
<b>Classification</b> Eye Dam. 1 - H318	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet cement or wet cement containing preparations.
<b>Inhalation</b>	Move affected person to fresh air at once. Dust in throat and nasal passages should clear spontaneously. Get medical attention if irritation persists or later develops, or if discomfort, coughing or other symptoms persist.
<b>Ingestion</b>	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Never give anything by mouth to an unconscious person. Get medical attention immediately.
<b>Skin contact</b>	Wash immediately with soap and water. Obtain medical advice if skin disorders develop.
<b>Eye contact</b>	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
<b>Ingestion</b>	Ingestion of large doses may result in irritation to the gastrointestinal tract.
<b>Skin contact</b>	May cause an allergic skin reaction. May cause skin disorders if contact is repeated or prolonged.
<b>Eye contact</b>	Eye contact may cause serious and potentially irreversible injuries.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

### SECTION 5: Firefighting measures

## Patchroc 250

### 5.1. Extinguishing media

**Suitable extinguishing media** The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Water used for fire extinguishing, which has been in contact with the product, may be corrosive. No unusual fire or explosion hazards noted.

**Hazardous combustion products** No known hazardous decomposition products.

### 5.3. Advice for firefighters

**Protective actions during firefighting** No specific firefighting precautions known.

**Special protective equipment for firefighters** Use protective equipment appropriate for surrounding materials.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use work methods which minimize dust production. Avoid contact with eyes and prolonged skin contact. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of dust.

### 6.2. Environmental precautions

**Environmental precautions** Collect and dispose of spillage as indicated in Section 13. Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into suitable waste disposal containers and seal securely. Wet material: Clean up wet material and place in a container. Allow to dry and solidify before disposal as described in section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid contact with skin and eyes. Avoid generation and spreading of dust. Avoid inhalation of dust. Mechanical ventilation or local exhaust ventilation may be required. Change contaminated clothing. Do not eat, drink or smoke when using the product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry and cool place. Unsuitable container materials: Aluminium. The product contains less than 2 mg chromate/kg dry cement, and this limit will not be exceeded for 6 months from the packing date stated on the packaging. Seal opened containers and use up as soon as possible To be stored out of reach of children in its original packaging in a dry place.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

## Patchroc 250

### CEMENT POWDER

Long-term exposure limit (8-hour TWA): WEL 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup> respirable dust

### SILICA SAND

Long-term exposure limit (8-hour TWA): WEL 0,1 mg/m<sup>3</sup> Respirable crystalline silica

### Calcium Carbonate - Limestone (13 Micron)

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m<sup>3</sup> respirable dust

### CALCIUM SULFOALUMINATE

Long-term exposure limit (8-hour TWA): 10 mg/m<sup>3</sup> inhalable dust

Long-term exposure limit (8-hour TWA): 4 mg/m<sup>3</sup> respirable dust

### CALCIUM CARBONATE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup>

### CALCIUM SULPHATE B-ANHYDRITE

Long-term exposure limit (8-hour TWA): TLV - Threshold Limit Value 10 mg/m<sup>3</sup>

### TARTARIC ACID POWDER

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup> resp.dust

WEL = Workplace Exposure Limit

### CEMENT POWDER (CAS: 65997-15-1)

DNEL

Workers - Inhalation; Short term : 3 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Atmospheric levels of dust must be maintained within the Occupational Exposure Limit. Where mechanical methods are inadequate or impractical, appropriate personal protective equipment must be used.

#### Personal protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. This product may present a chromate (VI) allergy risk. It contains a chromate reducing agent, but users should wear appropriate personal protective equipment.

#### Eye/face protection

The following protection should be worn: Chemical splash goggles. (conform EN 166)

#### Hand protection

Use impervious, abrasion and alkali resistant gloves. Nitrile rubber. Butyl rubber.

#### Other skin and body protection

Use barrier creams to prevent skin contact. Wear appropriate clothing to prevent repeated or prolonged skin contact.

#### Hygiene measures

This product contains silica sands.

The grain size distribution of silica sand present means that it is not classified as hazardous. However, any respirable crystalline dust generated by secondary processing may cause health effects.

Prolonged and /or massive inhalation of respirable crystalline silica dust may cause lung fibrosis, commonly referred to as silicosis. Principal symptoms of silicosis are cough and breathlessness.

Occupational exposure to respirable crystalline silica dust should be monitored and controlled

## Patchroc 250

**Respiratory protection**      Wear a respirator fitted with the following cartridge: Particulate filter, type P2.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Powder.
<b>Colour</b>	Grey.
<b>Odour</b>	Odourless.
<b>Odour threshold</b>	Not relevant.
<b>pH</b>	pH (concentrated solution): >12
<b>Melting point</b>	>1250°C
<b>Initial boiling point and range</b>	Not applicable.
<b>Flash point</b>	Not applicable.
<b>Evaporation rate</b>	Not applicable.
<b>Evaporation factor</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	The product is not flammable.
<b>Other flammability</b>	Not applicable.
<b>Vapour pressure</b>	Not applicable.
<b>Vapour density</b>	Not applicable.
<b>Relative density</b>	Not determined.
<b>Bulk density</b>	Not determined.
<b>Solubility(ies)</b>	Slightly soluble in water. Hardens in contact with water.
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	Not applicable.
<b>Explosive properties</b>	Not considered to be explosive.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

#### 9.2. Other information

**Other information**      Not available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity**      When mixed with water, hardens to form a stable mass that is not reactive in normal conditions.

## Patchroc 250

### 10.2. Chemical stability

#### Stability

Stable under the prescribed storage conditions. When stored under humid conditions, the chromate neutralization will decrease. This product contains a chromate reducing agent to reduce the risk of allergic dermatitis caused by chromium (VI). This product has a shelf life. If not stored in accordance with packaging instructions (sealed and dry), there is an increased risk of the presence of hexavalent chromate leading to an increased risk of an allergic reaction.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None known. Will not polymerise.

### 10.4. Conditions to avoid

**Conditions to avoid** Water, moisture.

### 10.5. Incompatible materials

**Materials to avoid** Acids. Chemically-active metals.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** No known hazardous decomposition products.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Skin sensitisation

**Skin sensitisation** Some individuals may exhibit eczema upon exposure to wet cement caused either by the high pH which induces irritant contact dermatitis, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis. The cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness is not exceeded, a sensitising effect is not expected.

#### Inhalation

Irritating to respiratory system. Inflammation of the nasal mucous membrane by exposure to cement dust.

#### Ingestion

May cause irritation of mouth, throat and digestive tract.

#### Skin contact

This product is strongly irritating. Prolonged contact may cause burns. May cause sensitisation by skin contact.

#### Eye contact

Irritating and may injure eye tissue if not removed promptly.

#### Acute and chronic health hazards

Repeated and/or prolonged contact may lead to dermatitis.

### Toxicological information on ingredients.

#### CEMENT POWDER

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub>)** 2,000.0 mg/kg

**Species** Rabbit

#### SILICA SAND ( 0,1 - 0,15 mm)

##### Carcinogenicity

## Patchroc 250

**IARC carcinogenicity** IARC Group 1 Carcinogenic to humans.

### CALCIUM SULPHATE B-ANHYDRITE

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> 3000 mg/kg, Oral, Rat

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Chronic alveolar can be seen from the neutrophils or the alveolar wall.

### SECTION 12: Ecological Information

**Ecotoxicity** The product is not expected to be hazardous to the environment.

#### 12.1. Toxicity

##### Acute aquatic toxicity

##### Acute toxicity - fish

Not determined.

The product is not expected to be hazardous to the environment. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.

#### Ecological information on ingredients.

### CEMENT POWDER

#### Acute aquatic toxicity

##### Acute toxicity - fish

Not determined.

### CALCIUM SULPHATE B-ANHYDRITE

#### Acute aquatic toxicity

##### Acute toxicity - fish

LC<sub>50</sub>, 96 hours: 2980 mg/l, Lepomis macrochirus (Bluegill)

##### Acute toxicity - aquatic invertebrates

LC<sub>50</sub>, 48 hours: 1910 mg/l, Ceriodaphnia dubia(물벼룩류)

##### Acute toxicity - aquatic plants

EC<sub>50</sub>, 96 hours: 3200 mg/l, Navicula seminulum(Diatom)

#### 12.2. Persistence and degradability

**Persistence and degradability** The product is not biodegradable.

#### 12.3. Bioaccumulative potential

##### Bioaccumulative potential

The product is not bioaccumulating.

##### Partition coefficient

Not determined.

#### 12.4. Mobility in soil

##### Mobility

The product hardens to a solid, immobile substance. The product is not volatile but may be spread by dust-raising handling.

#### 12.5. Results of PBT and vPvB assessment

##### Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

##### Other adverse effects

None known.



## Patchroc 250

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	Do not empty into drains, sewers or water courses. Cement that has exceeded its shelf life: when demonstrated that it contains more than 0.0002% Cr (VI), the product shall not be used other than in controlled closed and totally automated processes. It may be recycled and/or treated again with a reducing agent.
<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Note that fully cured material is not considered as hazardous waste.

### SECTION 14: Transport information

<b>General</b>	The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).
----------------	--

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**  
No.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).
<b>EU legislation</b>	Commission Regulation (EU) No 453/2010 of 20 May 2010. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

#### 15.2. Chemical safety assessment

## Patchroc 250

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>General information</b>	For professional users only. Only trained personnel should use this material.
<b>Revision comments</b>	This is first issue.
<b>Revision date</b>	09/02/2018
<b>Revision</b>	0
<b>Supersedes date</b>	27/04/2015
<b>SDS number</b>	26148
<b>Hazard statements in full</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.