

DECLARATION OF PERFORMANCE

Ng. DOP-08-07/21

1. Unique identification code of the product-type:
StyroFix Universal – Grey – fibre reinforced

2. Intended use:
General purpose mortar (GP) for thermal insulation boards

3. Authorised representative:
Fragmat Mak Doo
Industrial Zone Karpos, Str.221, n175, 1300, Kumanovo
Part of Fragmat Group Slovenia (www.fragmat.si)

4. System of AVCP:
System 4 (Factory made rendering/plastering mortars)
 - 4a. Harmonised standard:
EN 998-1:2016 and EN 13499:2003

 - 4b. European Assessment Document:
not relevant

 - European Technical Assessment:
not relevant

 - Technical Assessment body
Testing Laboratory Directorate EUROTTEST – CONTROL EAD, 1517 Sofia, Bulgaria,

 - Notified body:
not relevant

7. Declared performance

| Essential characteristics | Performance | Test Method | Harmonised Technical specification |
|--|---|-------------------|------------------------------------|
| Compressive strength | CS IV | EN 1015-11:2019 | EN 998-1:2016 |
| Reaction to fire | class A1 | EN 13501-1 | |
| Water absorption coefficient | 0.18 kg /(m ² *min ^{0.5}) | EN 1015-18:2002 | |
| Flexural strength | 3.8 N/mm ² | EN 1015-11:2019 | |
| Adhesion of mortar on concrete substrate | ≥1.3 N/mm ² (FP:A) | EN 1015 – 12:2016 | |
| Durability | evaluation based on provisions valid in the intended place of use of the mortar | | |

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

21.07.2020

Faruk Ali
Quality Manager