

DECLARATION OF PERFORMANCE

Ng. DOP-09-07/21

1. Unique identification code of the product-type:
StyroFix Universal – White – fibre reinforced
2. Intended use:
General purpose mortar (GP) for thermal insulation boards
3. Authorised representative:
Fragmat Mak Doo
Industrial Zone Karpos, Str.221, n175, 1300, Kumanovo
Part of Fragmat Group Slovenia (www.fragmat.si)
4. System of AVCP:
System 4 (Factory made rendering/plastering mortars)
 - 4a. Harmonised standard:
EN ISO 998-1:2016 and EN 13499:2004
 - 4b. European Assessment Document:
not relevant
 - European Technical Assessment:
not relevant
 - Technical Assessment body
Testing Laboratory Directorate EUROTTEST – CONTROL EAD, 1517 Sofia, Bulgaria,
 - Notified body:
not relevant

5. Declared performance

Essential characteristics	Performance	Test Method	Harmonised Technical specification
Compressive strength	CS IV	EN 1015-11:2020	EN ISO 998-1:2016
Reaction to fire	class A1	EN 13501-1	
Capillary water absorption	0.16 kg /(m ² *min ^{0.5})	EN 1062-3:2008	
Flexural strength	4.1 N/mm ²	EN 1015-11:2019	
Adhesion of mortar on concrete substrate	≥ 1,4 N/mm ² (FP:A)	EN 1015-12	
Durability	evaluation based on provisions valid in the intended place of use of the mortar		

6. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

21.07.2020

Faruk Ali
Quality Manager