

Technical Data Sheet

General Description

The FibaTape® family includes a complete range of innovative drywall joint tapes and reinforcing products for both professionals and DIYers.

The FibaTape® Perfect Finish is self-adhesive tape specially woven to be thinner than FiberTape® Classic while keeping the same strength. It is the best solution for ceiling or square edge plasterboards.

Properties

- Thinner profile (- 30 %)
- Less compound
- Self-adhesive
- High mechanical strength
- Smooth finish

Technical Characteristics

Technical Characteristics		
Setting of the fiberglass yarns (informative value)	Warp	Weft
	79 ends / 10 cm 20,1 ends / inch	39 ends / 10 cm 9,9 ends / inch
Treated fabric weight (incl. glue) (informative value)	(70,0 ± 1,5) g / m ² (2,06 ± 0,04) oz / yd ²	
DPU (PES + coating + PSA) (informative value)	23 – 26 %	
Thickness (informative value)	0,14 mm	
	0,006 inch	
Tensile strength	Warp	Weft
	476 N / 2,54 cm 105 lbs / inch	502 N / 2,54 cm 111 lbs / inch
Dimensions & Packaging		
Standard width ⁽¹⁾ (individual value)	48 ± 2 mm	
	1,89 ± 0,08 inch	
Standard roll length ⁽¹⁾ (individual value)	90 m (± 2 %)	
	98,43 yd (± 2 %)	
Rolls / box ⁽¹⁾	12	
Rolls / pallet ⁽¹⁾	480 (40 boxes)	
Storage conditions	Dry room, storing temperature from -10 °C to +50 °C.	
Pallet (non-returnable) ⁽¹⁾	80 x 120 x 100 cm	
Quality Control		
Traceability ⁽¹⁾	Batch no. marked on the box	



Edited by:

ADFORS Construction Products Europe

SAINT-GOBAIN ADFORS CZ s.r.o.

Sokolovska 106

CZ – 570 01 Litomysl

Tel: + 420 461 651 111

Fax: + 420 461 612 769

www.adfors.com

ADFORS Construction Products Europe reserves the right to change the information given herein without prior notice

Last update: 12.12.2017

⁽¹⁾ Other dimension or features on request