

# DECLARATION OF PERFORMANCE

Ng. DOP-10-07/20

1. Unique identification code of the product-type:  

**Quartz grund**  
Acrylic adhesion primer for renders,
2. Intended use:  

**Ready-to-use base coat of renders for interior and exterior applications.**
3. Authorised representative:  

**Fragmat Mak Doo**  
Industrial zone - Karposh, Kumanovo, 1300  
Part of Fragmat Group Slovenia ([www.fragmat.si](http://www.fragmat.si))
4. System of AVCP:
  - 6a. Harmonised standard:  

**Not relevant**
  - 6b. European Assessment Document:  

**not relevant**
  - European Technical Assessment:  

**not relevant**
  - Technical Assessment body  

**not relevant**
  - Notified body:  

**not relevant**

7. Declared performance

Essential characteristics	Performance	Test Method	Harmonised Technical specification
Temperature conditions - surface and air (R.h. < 80%, protected against sun, wind and rainfall with curtains)	between (+)5 °C - (+)35 °C - do not conduct any work in rain, fog or strong wind (≥30 km/h).	MDV	MD Values
Dilution	max 10% if necessary (with clear water)	MDV	
Drying time (+20 °C, r. h. 65 %)	~ 2 hours (touch dry)	MDV	
	4 – 6 hours (suitable for further treatment)	MDV	
Resistance to precipitation (washing away of the Application ) (+20 °C, r. h. 65 %)	~ 24 hours	MDV	

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

01.07.2020

**Faruk Ali**  
Quality Manager