



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** **MC-DUR TopSpeed M - Komponente A**

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture**

Sealing

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07

· **Signal word**

Warning

· **Hazard-determining components of labelling:**

tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate
Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester

(Contd. on page 2)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 1)

- **Hazard statements** 4-morpholinecarbaldehyde
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 136210-30-5 ELINCS: 429-270-1 Reg.nr.: 01-0000017556-64-XXXX	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl) bis-DL-aspartate Skin Sens. 1, H317; Aquatic Chronic 3, H412	30-60%
CAS: 108-32-7 EINECS: 203-572-1	Propylene carbonate Eye Irrit. 2, H319	<10%
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥0.25-<1.5%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<1.5%
CAS: 70969-70-9 EINECS: 275-073-7 Reg.nr.: 01-2120118956-48	2-Ethylhexyl-3,5,5-trimethylhexanoat STOT RE 2, H373	<1.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40-XXXX	Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.25-<1%
CAS: 4394-85-8 EINECS: 224-518-3 Reg.nr.: 01-2119987993-12	4-morpholinecarbaldehyde Skin Sens. 1, H317	≥0.1-<0.5%

(Contd. on page 3)



BE SURE. BUILD SURE.

Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **After inhalation** Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 3)

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require monitoring at the workplace:**

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value:	548 mg/m ³ , 100 ppm
	Long-term value:	274 mg/m ³ , 50 ppm
Sk		

· **DNELs**

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Dermal	DNEL	4 mg/kg bw/day (ArL)
Inhalative	DNEL	28 mg/m ³ (ArL)
		112 mg/m ³ (Ark)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Dermal	DNEL	153.5 mg/kg bw/day (ArL)
Inhalative	DNEL	275 mg/m ³ (ArL)

· **PNECs**

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

PNEC	31.1 mg/l (Kla)
	0.000013 mg/l (Mew)
	0.00013 mg/l (Freshwater)
PNEC	0.1 mg/kg dwt (Bod)

(Contd. on page 5)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 4)

	0.02 mg/kg dwt (Marine water sediment)
	0.21 mg/kg dwt (Fresh water sediment)
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	
PNEC	0.635 mg/l (Fresh water)
	100 mg/l (Kla)
	0.0635 mg/l (Mew)
PNEC	0.29 mg/kg dwt (Bod)
	0.329 mg/kg dwt (Marine water sediment)
	3.29 mg/kg dwt (Fresh water sediment)

- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
 - Keep away from foodstuffs, beverages and food.
 - Instantly remove any soiled and impregnated garments.
 - Wash hands during breaks and at the end of the work.
 - Avoid contact with the eyes and skin.
 - Do not eat, drink or smoke while working.
- **Breathing equipment:** Breathing protection recommended.
- **Hand protection**
 - Conditionally suitable materials for protective gloves; EN 374-3: Nitrile rubber - NBR: Thickness $\geq 0.35\text{mm}$.
 - Only suitable for splash protection. Only suitable for short-term exposure. In case of contamination, the protective gloves must be changed immediately.
 - Protective gloves.
 - Nitrile rubber, NBR
- **Material of gloves**
- **Penetration time of glove material**
 - The exact breakthrough time must be obtained from the protective glove manufacturer and must be observed.
- **Eye/face protection**
 - Safety glasses
 - Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Colour:** Cloudy
- **Smell:** Product specific
- **Odour threshold:** Not determined.

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 5)

· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	185 °C (CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	100 °C
· Auto-ignition temperature:	350 °C (CAS: 152637-10-0 poly(oxy(methyl-1,2-ethanediyl)))
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	3000-5000 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined.
· Steam pressure at 20 °C:	2 hPa (CAS: 152637-10-0 poly(oxy(methyl-1,2-ethanediyl)))
· Vapour pressure at 50 °C:	8 hPa
· Density and/or relative density	
· Density at 20 °C	1.15 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Viscous
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Change in condition	
· Evaporation rate	Not determined.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void

(Contd. on page 7)

GB



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 6)

- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

Oral LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.1)

Dermal LD50 >2000 mg/kg (rat) (67/548/EWG, Annex V, B.3)

CAS: 108-32-7 Propylene carbonate

Oral LD50 >5000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rabbit)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8500 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)



BE SURE. BUILD SURE.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 7)

- **STOT-single exposure** *Based on available data, the classification criteria are not met.*
- **STOT-repeated exposure** *Based on available data, the classification criteria are not met.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 128-37-0 2,6-Di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 136210-30-5 tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate

LC50/96h	66 mg/l (Danio rerio) (OECD 203)
EC50	3110 mg/l (BEL)
EC50/48h	88.6 mg/l (Daphnia magna)
NOEC	0.01 mg/l (Daphnia magna)
ErC50/72h	113 mg/l (Scenedesmus subspicatus)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

LC50/96h	134 mg/l (Oncorhynchus mykiss) 161 mg/l (Pimephales promelas)
EC50	>1000 mg/l (BEL)
EC50/48h	>500 mg/l (Daphnia magna)
NOEC	47.5 mg/l (Ory)
EC50/3d	>1000 mg/l (Selenastrum capricornutum)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Remark:**

Harmful to fish

· **Additional ecological information:**

· **General notes:**

Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

GB

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 8)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name	
· ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/ legislation specific for the substance or mixture** *No further relevant information available.*
- **Poisons Act**

· Regulated explosives precursors	
<i>None of the ingredients is listed.</i>	
· Regulated poisons	
<i>None of the ingredients is listed.</i>	
· Reportable explosives precursors	
<i>None of the ingredients is listed.</i>	

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 9)

· Reportable poisons

None of the ingredients is listed.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. on page 11)



BE SURE. BUILD SURE.

Page 11/11

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.01.2024

Version number 20 (replaces version 19)

Revision: 12.01.2024

Trade name MC-DUR TopSpeed M - Komponente A

(Contd. of page 10)

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.

GB