

Page 1/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name MC-Color Flex pure

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance

/ the mixture Dispersion paint/ Latex paint

Surface protection

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

> Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department:

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

msds@mc-bauchemie.de

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS07

· Signal word Warning

Hazard-determining

components of labelling: 2-methyl-2H-isothiazol-3-one

(Contd. on page 2)





Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 1)

1,2-benzisothiazol-3(2H)-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6]

(3:1)

· **Hazard statements** H317 May cause an allergic skin reaction.

· **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before

reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/

attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with

local/regional/national/international regulations.

· Additional information: EUH211 Warning! Hazardous respirable droplets may be formed

when sprayed. Do not breathe spray or mist.

Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-

3-one [EC no. 220-239-6] (3:1)

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components.

· Dangerous components:				
CAS: 1317-65-3	Calcium carbonate substance with a Community workplace exposure limit	10-30%		
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	10-30%		
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥0.05 %	≥0.025-<0.05%		
	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.0015 %	<i>≥</i> 0.0015-<0.025%		

1900



Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 2)

CAS: 55965-84-9 | reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one | ≥0.00025-<0.0015%

[EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one

[EC no. 220-239-6] (3:1)

Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410

(M=100); Skin Sens. 1A, H317, EUH071

Specific concentration limits: Skin Corr. 1C; H314: C ≥0.6 %

Skin Irrit. 2; H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1; H318: $C \ge 0.6\%$

Eye Irrit. 2; H319: $0.06 \% \le C < 0.6 \%$ Skin Sens. 1A; H317: $C \ge 0.0015 \%$

Additional information For the wording of the listed hazard phrases refer to section 16.

Acrylic dispersion

Chalk Water

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information No special measures required.

• After inhalation Supply fresh air.

• After skin contact The product is not skin irritating.

• After eye contact Rinse opened eye for several minutes under running water.

• After swallowing Rinse out mouth and then drink plenty of water.

Seek medical treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or

mixture No further relevant information available.

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Not required.

· 6.2 Environmental

precautions: Dilute with much water.

(Contd. on page 4)



Page 4/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 3)

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

· 6.4 Reference to other

sections No dangerous materials are released.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling No special measures required.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Not required.

· Further information about

storage conditions: None.
Storage class 12

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 1317-65-3 Calcium carbonate

WEL Long-term value: 10* 4** mg/m³
*inhalable dust; **respirable

· DNELs

CAS: 1317-65-3 Calcium carbonate

Oral DNEL 6.1 mg/kg bw/Tag (ArL)
Inhalative DNEL 10 mg/m³ (ArL)

PNECs

CAS: 1317-65-3 Calcium carbonate

PNEC 100 mg/l (Sewage Treatment Plant)

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering

controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and

hygienic measures The usual precautionary measures should be adhered to in

handling the chemicals.

(Contd. on page 5)



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 4)

Breathing equipment: Not required.Hand protection Not required.

· Material of gloves · Penetration time of glove

material

· Eye/face protection Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: According to product specification

· Smell: Characteristic · Melting point/freezing point: Not determined

Boiling point or initial boiling point and

boiling range 100 °C (CAS: 7732-18-5 water, distilled,

conductivity or of similar purity)

· Flash point: Not applicable

· pH at 20 °C

· Viscositv:

Kinematic viscositydynamic at 20 °C:Not determined.32500 mPas

Solubility

Water: Fully miscible

· Steam pressure at 20 °C: 23 hPa (CAS: 7732-18-5 water, distilled,

conductivity or of similar purity)

· Density and/or relative density

• Density at 20 °C 1.42 g/cm³ • Relative density Not determined.

· 9.2 Other information

Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

• Self-inflammability: Product is not selfigniting. • Explosive properties: Product is not explosive.

· Information with regard to physical hazard

classes · Explosives Void Flammable gases Void Void · Aerosols Void · Oxidising gases Void · Gases under pressure Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 29 (replaces version 28) Revision: 21.06.2024 Printing date 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 5)

· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability · Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

· 10.4 Conditions to avoid No further relevant information available. · 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

CAS: 131	7-65-3 Cal	lcium carbonate
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 134	63-67-7 tit	tanium dioxide
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)
CAS: 263	4-33-5 1,2	-benzisothiazol-3(2H)-one
Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
CAS: 268	2-20-4 2-m	nethyl-2H-isothiazol-3-one
Oral	LD50	50-300 mg/kg (rat)
		(Contd. on



Page 7/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 6)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

 Oral
 LD50
 49.6-75 mg/kg (rat)

 Dermal
 LD50
 87.12 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 0.171 mg/l (rat)

Inhalative LC50/4 h 0.11 mg/l (rat)

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

Respiratory or skin

sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Aspiration hazard
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

· Aspiration hazard Bas · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 1317-65-3 Calcium carbonate

EC50/72h >14 mg/l (Desmodesmus subspicatus)

LC50/96h >10000 mg/l (Oncorhynchus mykiss)

LC50/48h >1000 mg/l (Daphnia magna)

EC50/48h >1000 mg/l (Daphnia magna)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/72h 0.067 mg/l (Pseudokirchneriella subcapitata)

0.11 mg/l (Selenastrum capricornutum)

LC50/96h 1.6 mg/l (Oncorhynchus mykiss)

EC50/48h 1.1 mg/l (Daphnia magna)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

EC50/72h | 0.157 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 6 mg/l (Oncorhynchus mykiss)

EC50/48h 1.68 mg/l (Daphnies)

CAS: 55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

LC50/24h | 0.19 mg/l (fish)

EC50/72h | 0.027 mg/l (Pseudokirchneriella subcapitata)

(Contd. on page 8)



Page 8/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 7)

LC50/96h | 0.19 mg/l (Oncorhynchus mykiss)

LC50/48h 0.28 mg/l (fish)

EC50/48h 0.16 mg/l (Daphnia magna)

NOEC 0.02 mg/l (Oncorhynchus mykiss)

0.00049 mg/l (Ske)

0.1 mg/l (Daphnia magna)

· 12.2 Persistence and

degradability No further relevant information available.

12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Endocrine disrupting

properties The product does not contain substances with endocrine disrupting

properties.

· 12.7 Other adverse effects

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach

ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

· Recommended cleaning

agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

Class

(Contd. on page 9)



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 29 (replaces version 28) Revision: 21.06.2024 Printing date 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 8)

	(Conta. or page o
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/ legislation specific for the

substance or mixture No further relevant information available.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

arry specific product realure	es and snan n	ot establish a legally valid contractual relations
· Relevant phrases	H301	Toxic if swallowed.
•	H302	Harmful if swallowed.
	H310	Fatal in contact with skin.

H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317

Causes serious eye damage. H318

(Contd. on page 10)



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.06.2024 Version number 29 (replaces version 28) Revision: 21.06.2024

Trade name MC-Color Flex pure

(Contd. of page 9)

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H351 Suspected of causing cancer. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard -

Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic

hazard - Category 1

^{· *} Data compared to the previous version altered.