



BE SURE. BUILD SURE.

Page 1/13

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** MC-DUR 1320 VK - Komponente A

· **Article number:** 4067

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Epoxy coating

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

· **Informing department:** msds@mc-bauchemie.de

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360F May damage fertility.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure.
Route of exposure: Inhalation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 1)

· Hazard pictograms



GHS07 GHS08 GHS09

· Signal word

Danger

· Hazard-determining components of labelling:

epoxide derivates
crystalline silica
Alkyl Glycidyl Ether
maleic anhydride

· Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H360F May damage fertility.
H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.

· Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components.

· Dangerous components:

CAS: 1675-54-3	epoxide derivates	30-60%
EINECS: 216-823-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	

(Contd. on page 3)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 2)

CAS: 14808-60-7	crystalline silica STOT RE 1, H372	10-30%
CAS: 68609-97-2	Alkyl Glycidyl Ether Repr. 1B, H360F; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<5%
CAS: 100-51-6	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<2.5%
CAS: 108-31-6 EINECS: 203-571-6	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<0.001%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur.
If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water.
Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

· **4.2 Most important symptoms and effects, both acute and delayed**

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)



BE SURE. BUILD SURE.

Page 4/13

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:** Prevent material from reaching sewage system, holes and cellars.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Open and handle containers with care.
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.
- **Information about protection against explosions and fires:** Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Further information about storage conditions:** Keep container tightly closed in a well-ventilated place.
- **Storage class** 6.1C

GB

(Contd. on page 5)



BE SURE. BUILD SURE.

**Safety data sheet
according to UK REACH**

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

CAS: 108-31-6 maleic anhydride

WEL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ Sen
-----	--

· DNELs

CAS: 68609-97-2 Alkyl Glycidyl Ether

Dermal	DNEL	0.75 mg/kg bw/day (ArL)
Inhalative	DNEL	0.49 mg/m ³ (ArL)

CAS: 100-51-6 Benzyl alcohol

Oral	DNEL	4 mg/kg bw/Tag (ArL)
		20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL)
		40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m ³ (ArL)
		110 mg/m ³ (Ark)

· PNECs

CAS: 68609-97-2 Alkyl Glycidyl Ether

PNEC	0.00072 mg/l (Mew)
	0.0072 mg/l (Freshwater)
PNEC	80.12 mg/kg dwt (Bod)
	6.677 mg/kg dwt (Sediment)
	66.77 mg/kg dwt (Fresh water sediment)

CAS: 100-51-6 Benzyl alcohol

PNEC	0.527 mg/l (Marine water sediment)
	0.1 mg/l (Mew)
	1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod)
	5.27 mg/kg dwt (Fresh water sediment)

· Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls

No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

(Contd. on page 6)



BE SURE. BUILD SURE.

Page 6/13

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

- (Contd. of page 5)
- **Breathing equipment:** *If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.*
 - **Hand protection** *Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
 - **Material of gloves** *You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.
Nitrile rubber
Recommended material thickness: ≥ 0.4 mm*
 - **Penetration time of glove material** *The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.
The following applies to all other gloves:
The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.
Nitrile rubber
Material thickness: ≥ 0.40 mm
Penetration time: ≥ 480 min
Butyl rubber:
Material thickness: ≥ 0.5 mm
Penetration time: ≥ 480 min*
 - **Eye/face protection** *Tight-fitting safety goggles.
Safety goggles.*
 - **Body protection:** *Protective clothing
Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.*

GB

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/13

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour:	Colourless
· Smell:	Characteristic
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	2230 °C (CAS: 14808-60-7 Quartz (SiO ₂))
· Flash point:	>61 °C
· Auto-ignition temperature:	184 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	8000 mPas
· Solubility	
· Water:	Not miscible or difficult to mix
· Steam pressure at 20 °C:	0 hPa (CAS: 1675-54-3 epoxide derivates)
· Density and/or relative density	
· Density at 20 °C	1.67 g/cm ³

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void

(Contd. on page 8)

GB



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 7)

· **Desensitised explosives**

Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 1675-54-3 epoxide derivatives

Dermal	LD50	23000 mg/kg (rabbit)
--------	------	----------------------

CAS: 68609-97-2 Alkyl Glycidyl Ether

Oral	LD50	17100 mg/kg (rat)
------	------	-------------------

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 108-31-6 maleic anhydride

Oral	LD50	1090 mg/kg (rat)
Dermal	LD50	2620 mg/kg (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** May damage fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

(Contd. on page 9)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 8)

- **Aspiration hazard** *Based on available data, the classification criteria are not met.*
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

CAS: 128-37-0	2,6-Di-tert-butyl-p-cresol	List II
CAS: 556-67-2	Octamethylcyclotetrasiloxane	List II; III

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 1675-54-3 epoxide derivates

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss)
EC50/48h	1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)

CAS: 68609-97-2 Alkyl Glycidyl Ether

EbC50/72h	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>5000 mg/l (Oncorhynchus mykiss) 1800 mg/l (Lepomis macrochirus)
EC50	>100 mg/l (BEL)
NOEC	500 mg/l (Pseudokirchneriella subcapitata)

CAS: 100-51-6 Benzyl alcohol

IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas) 10 mg/l (Lepomis macrochirus)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 9)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **Uncleaned packagings:**

· **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA** UN3082

· **14.2 UN proper shipping name**

· **ADR, IATA** ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (epoxide derivates)
· **IMDG** ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (epoxide derivates,
Alkylbenzene), MARINE POLLUTANT

· **14.3 Transport hazard class(es)**

· **ADR**
· **Class** 9 (M6) Miscellaneous dangerous substances and
articles.
· **Label** 9

· **IMDG, IATA**

· **Class** 9 Miscellaneous dangerous substances and
articles.
· **Label** 9

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** Yes
Symbol (fish and tree)
· **Special marking (ADR):** Symbol (fish and tree)
· **Special marking (IATA):** Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Miscellaneous dangerous substances and
articles.
· **Kemler Number:** 90
· **EMS Number:** F-A,S-F
· **Stowage Category** A

· **14.7 Maritime transport in bulk according to
IMO instruments**

Not applicable.

(Contd. on page 11)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· Transport category

3

· Tunnel restriction code

(-)

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (EPOXIDE
DERIVATES), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Qualifying quantity (tonnes)
for the application of lower-
tier requirements

200 t

· Qualifying quantity (tonnes)
for the application of upper-
tier requirements

500 t

(Contd. on page 12)



BE SURE. BUILD SURE.

Safety data sheet according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 11)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.*
- H314 Causes severe skin burns and eye damage.*
- H315 Causes skin irritation.*
- H317 May cause an allergic skin reaction.*
- H318 Causes serious eye damage.*
- H319 Causes serious eye irritation.*
- H332 Harmful if inhaled.*
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
- H360F May damage fertility.*
- H372 Causes damage to organs through prolonged or repeated exposure.*
- H411 Toxic to aquatic life with long lasting effects.*
- EUH071 Corrosive to the respiratory tract.*
- EUH205 Contains epoxy constituents. May produce an allergic reaction.*

· Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*
- ICAO: International Civil Aviation Organisation*
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*
- IMDG: International Maritime Code for Dangerous Goods*
- IATA: International Air Transport Association*
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
- EINECS: European Inventory of Existing Commercial Chemical Substances*
- ELINCS: European List of Notified Chemical Substances*
- CAS: Chemical Abstracts Service (division of the American Chemical Society)*
- DNEL: Derived No-Effect Level (UK REACH)*
- PNEC: Predicted No-Effect Concentration (UK REACH)*
- LC50: Lethal concentration, 50 percent*
- LD50: Lethal dose, 50 percent*
- PBT: Persistent, Bioaccumulative and Toxic*
- vPvB: very Persistent and very Bioaccumulative*
- Acute Tox. 4: Acute toxicity – Category 4*
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B*
- Skin Irrit. 2: Skin corrosion/irritation – Category 2*
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1*
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*
- Resp. Sens. 1: Respiratory sensitisation – Category 1*
- Skin Sens. 1: Skin sensitisation – Category 1*
- Skin Sens. 1A: Skin sensitisation – Category 1A*
- Repr. 1B: Reproductive toxicity – Category 1B*

(Contd. on page 13)



BE SURE. BUILD SURE.

Page 13/13

Safety data sheet
according to UK REACH

Printing date 28.07.2024

Version number 46 (replaces version 45)

Revision: 28.07.2024

Trade name MC-DUR 1320 VK - Komponente A

(Contd. of page 12)

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the
previous version altered.**

GB