



BE SURE. BUILD SURE.

Page 1/11

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **MC-DUR PowerCoat 200 - Komponente C**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Application of the substance / the mixture

Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG
Am Kruppwald 1-8
D-46238 Bottrop
Tel.: +49(0)2041-101-0
Fax.: +49(0)2041-101-400
E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG
Hagackerstr. 10
CH-8953 Dietikon
Tel.: +44-7400510
Fax : +44-7400533

Informing department: msds@mc-bauchemie.de

1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +1 872 5888271 (MCR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS08

Signal word

Danger

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 1)

- **Hazard-determining components of labelling:** Portland cement (low chromate)
Quartz sand
calcium oxide
- **Hazard statements** H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Precautionary statements** P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 65997-15-1 EINECS: 266-043-4	Portland cement (low chromate) Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	50-70%
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sand STOT RE 1, H372	30-60%
CAS: 1305-78-8 EINECS: 215-138-9	calcium oxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥3-<5%

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** Remove, decontaminate and dispose of soiled, soaked clothing and shoes immediately.
- **After inhalation** Remove person to fresh air, keep warm, allow to rest; if breathing is difficult, seek medical attention.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

· **After skin contact**

(Contd. of page 2)

In case of contact with skin, preferably wash with polyethylene glycol-based cleaner or clean with plenty of warm water and soap. Consult a doctor in case of skin reactions.

· **After eye contact**

Rinse the eyes with open eyelids for a sufficiently long time (at least 10 minutes) with water that is as lukewarm as possible. Consult an ophthalmologist.

· **After swallowing**

Do NOT induce vomiting. Rinse mouth with water. Medical attention required.

· **4.2 Most important symptoms and effects, both acute and delayed**

Information for the doctor: The product irritates the respiratory tract and is a potential trigger for skin and respiratory sensitisation. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Depending on the extent of exposure and the symptoms, prolonged medical treatment may be necessary.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No information available.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*

· **5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

· **5.3 Advice for firefighters**

· **Protective equipment:**

No special measures required.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Not required.

· **6.2 Environmental precautions:**

No special measures required.

· **6.3 Methods and material for containment and cleaning up:**

Collect mechanically.

· **6.4 Reference to other sections**

*See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.*

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name **MC-DUR PowerCoat 200 - Komponente C**

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure sufficient air exchange and/or extraction in the work areas.
Air extraction is required for spray application.
For solid products: Avoid dust formation and dust deposits.
Air limit values mentioned in section 8 must be monitored.
At workplaces where isocyanate aerosols and/or vapours can occur in higher concentrations, targeted air extraction must be used to prevent the occupational hygiene limit value from being exceeded. The air must be moved away from people.
For products containing solvents: Explosion protection required.
The personal protective measures described in section 8 must be observed. The protective measures required when handling isocyanates must be observed. Avoid contact with skin and eyes and inhalation of vapours.
Keep away from food and beverages. Wash hands before breaks and at the end of work and apply skin protection ointment. Store work clothes separately. Remove soiled, soaked clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed. Further information on the storage conditions that must be observed for quality assurance reasons can be found in our technical data sheet.

Storage

Requirements to be met by storerooms and containers:

Store only in the original container.

Further information about storage conditions:

None.

Storage class

6.1C

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

CAS: 65997-15-1 Portland cement (low chromate)

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

CAS: 1305-78-8 calcium oxide

WEL Short-term value: 4* mg/m³
Long-term value: 2 1* mg/m³
*respirable fraction

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 4)

· **DNELs**

CAS: 65997-15-1 Portland cement (low chromate)

Inhalative DNEL 1 mg/m³ (ArL)

CAS: 1305-78-8 calcium oxide

Inhalative DNEL 1 mg/m³ (ArL)

· **PNECs**

CAS: 1305-78-8 calcium oxide

PNEC 2.27 mg/l (BEL)

0.24 mg/l (Mew)

0.37 mg/l (Freshwater)

PNEC 817.4 mg/kg dwt (Bod)

· **Additional information:**

The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.
Remove soiled, soaked clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with eyes and skin.

· **Breathing equipment:**

Respiratory protection required at insufficiently ventilated workplaces and when working with splashes. Fresh air masks or combination filters A2-P2 (EN529) are recommended for short-term work.

If applicable, further recommendations for respiratory protection can be found in the appendix.

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

· **Hand protection**

Suitable materials for protective gloves; EN 374:

Butyl rubber, nitrile rubber, chloroprene rubber (neoprene).

Note: suitable materials that provide sufficient protection for industrial cleaning with aprotic polar solvents (according to IUPAC definition): butyl rubber.

In case of prolonged or frequently repeated contact, a glove with a protection class of 5 or higher is recommended (breakthrough time greater than 240 minutes according to EN374). For short-term contact, a glove with a protection class of 3 or higher is recommended (breakthrough time greater than 60 minutes according to EN374).

The thickness of the material is not the only criterion for the level of protection of a glove against a chemical substance. The protective effect also depends to a large extent on the type of glove material. Depending on the type and material, the thickness must be more than 0.35 mm to ensure adequate protection in the event of prolonged and frequent contact. Exceptions to this rule are multi-layer gloves, which guarantee sufficient protection even with a

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

	(Contd. of page 5)
	thickness of less than 0.35 mm during prolonged wear. Other glove materials with a thickness of less than 0.35 mm only provide sufficient protection for short periods of wear.
	For solvent-free products:
	Example:
	Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
	Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$.
	Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$.
	Fluoro rubber - FKM: thickness $\geq 0.4\text{mm}$; breakthrough time $\geq 480\text{min}$.
	Recommendation: Dispose of contaminated gloves.
· Material of gloves	Polychloroprene - CR Nitrile rubber - NBR Butyl rubber - IIR Fluoro rubber - FKM
· Penetration time of glove material	Polychloroprene - CR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$. Nitrile rubber - NBR: thickness $\geq 0.35\text{mm}$; breakthrough time $\geq 480\text{min}$. Butyl rubber - IIR: thickness $\geq 0.5\text{mm}$; breakthrough time $\geq 480\text{min}$. Fluoro rubber - FKM: Thickness $\geq 0.4\text{mm}$; Breakthrough time $\geq 480\text{min}$.
· Eye/face protection	Safety goggles with side protection in accordance with EN 166.
· Body protection:	Use chemical-resistant protective clothing. In case of hypersensitivity of the skin, handling the product is not recommended.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Colour:	Grey
· Smell:	neutral
· Odour threshold:	Not determined.
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	2230 °C (CAS: 14808-60-7 Quartz sand)
· Flammability	Not determined.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable
· Decomposition temperature:	Not determined.
· pH	Not applicable.

(Contd. on page 7)



BE SURE. BUILD SURE.

Page 7/11

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 6)

· Viscosity:	
· Kinematic viscosity	Not applicable.
· dynamic:	Not applicable.
· Solubility	
· Water at 20 °C:	1.7 g/l
· Partition coefficient n-octanol/water (log value)	Not determined.
· Steam pressure at 1732 °C:	13.5 hPa (CAS: 14808-60-7 Quartz sand)
· Density and/or relative density	
· Density	Not determined
· Relative density	Not determined.
· Vapour density	Not applicable.

· 9.2 Other information

· Appearance:	
· Form:	Powder
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Molecular weight	74.09 g/mol
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes

· Explosives	Void
	Void
· Flammable gases	Void
	Void
· Aerosols	Void
	Void
· Oxidising gases	Void
	Void
· Gases under pressure	Void
	Void
· Flammable liquids	Void
	Void
· Flammable solids	Void
	Void
· Self-reactive substances and mixtures	Void
	Void
· Pyrophoric liquids	Void
	Void
· Pyrophoric solids	Void
	Void

(Contd. on page 8)

GB

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 7)

· Self-heating substances and mixtures	Void
	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
	Void
· Oxidising liquids	Void
	Void
· Oxidising solids	Void
	Void
· Organic peroxides	Void
	Void
· Corrosive to metals	Void
	Void
· Desensitised explosives	Void
	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 65997-15-1 Portland cement (low chromate)

Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	5 mg/l (rat)

CAS: 1305-78-8 calcium oxide

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2500 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **STOT-single exposure** May cause respiratory irritation.

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 8)

· **STOT-repeated exposure** Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 1305-78-8 calcium oxide

EC50/72h 184.57 mg/l (algae)

LC50/96h 50.6 mg/l (Fis)

158 mg/l (Mew)

EC50/48h 49.1 mg/l (Freshwater)

NOEC 32 mg/l (Mew)

48 mg/l (algae)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 9)

· **Recommended cleaning agent:**

Water, if necessary with cleaning agent.

SECTION 14: Transport information

- | | |
|---|-----------------|
| · 14.1 UN number or ID number | Void |
| · ADR, IMDG, IATA | |
| · 14.2 UN proper shipping name | |
| · ADR, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- | | |
|--|------------------------------------|
| · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture | |
| · Poisons Act | |
| · Regulated explosives precursors | |
| None of the ingredients is listed. | |
| · Regulated poisons | |
| None of the ingredients is listed. | |
| · Reportable explosives precursors | |
| None of the ingredients is listed. | |
| · Reportable poisons | |
| None of the ingredients is listed. | |
| · Directive 2012/18/EU | |
| · Named dangerous substances - ANNEX I | None of the ingredients is listed. |

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 15.04.2025

Version number 35 (replaces version 34)

Revision: 15.04.2025

Trade name MC-DUR PowerCoat 200 - Komponente C

(Contd. of page 10)

**15.2 Chemical safety
assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Relevant phrases

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

*** Data compared to the
previous version altered.**