



BE SURE. BUILD SURE.

Page 1/12

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

##### Trade name

**MC-DUR 1204 R - Komponente A**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Epoxy impregnation

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

MC-Bauchemie Müller GmbH & Co. KG  
Am Kruppwald 1-8  
D-46238 Bottrop  
Tel.: +49(0)2041-101-0  
Fax.: +49(0)2041-101-400  
E-Mail: [info@mc-bauchemie.de](mailto:info@mc-bauchemie.de)

MC-Bauchemie AG  
Hagackerstr. 10  
CH-8953 Dietikon  
Tel.: +44-7400510  
Fax : +44-7400533

##### Informing department:

[msds@mc-bauchemie.de](mailto:msds@mc-bauchemie.de)

#### 1.4 Emergency telephone number:

Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +1 872 5888271 (MCR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
Skin Sens. 1 H317 May cause an allergic skin reaction.  
Repr. 1A H360F May damage fertility.  
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS07 GHS08 GHS09

##### Signal word

Danger

(Contd. on page 2)

GB

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 1)

- **Hazard-determining components of labelling:** 4,4'-Methylenediphenyldiglycidyl ether  
1,6-bis(2,3-epoxypropoxy)hexane  
Cyclohexanol, 4,4'-(1-Methylethyliden)-, Polymer mit 2-(Chlormethyl)oxiran  
methyl toluene-4-sulphonate  
Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester
- **Hazard statements** H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H360F May damage fertility.  
H411 Toxic to aquatic life with long lasting effects.
- **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P405 Store locked up.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 1675-54-3	4,4'-Methylenediphenyldiglycidyl ether Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	50-70%
CAS: 30583-72-3 NLP: 500-070-7	Cyclohexanol, 4,4'-(1-Methylethyliden)-, Polymer mit 2-(Chlormethyl)oxiran Skin Sens. 1, H317	10-30%
CAS: 933999-84-9	1,6-bis(2,3-epoxypropoxy)hexane Repr. 1A, H360F; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<10%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	<5%

(Contd. on page 3)

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

CAS: 80-48-8 EINECS: 201-283-5	methyl toluene-4-sulphonate Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	(Contd. of page 2) ≥0.1-<1%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40-XXXX	Reaction mass of Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester and decanedioic acid, (1,2,2,6,6-pentamethyl-4-piperidiny) methyl ester Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.025-<0.1%

· **Additional information**

For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

- **General information** Remove contaminated clothing immediately. Consult a doctor if symptoms occur. Move affected person to fresh air.
- **After inhalation** Supply fresh air; seek medical advice if symptoms occur. If unconscious, place in recovery position and seek medical advice.
- **After skin contact** In case of contact with skin, wash carefully with plenty of soap and water. Consult a doctor in case of skin reactions.
- **After eye contact** Rinse opened eye for several minutes under running water. Call a doctor immediately
- **After swallowing** Rinse mouth with water. Never give anything by mouth to an unconscious person. DO NOT induce vomiting. If symptoms persist, consult a doctor.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Advice for the doctor: Elementary aid, decontamination, symptomatic treatment.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.

(Contd. on page 4)

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 3)

· **6.2 Environmental precautions:**

*Inform respective authorities in case product reaches water or sewage system.*

· **6.3 Methods and material for containment and cleaning up:**

*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*

· **6.4 Reference to other sections**

*See Section 7 for information on safe handling  
See Section 8 for information on personal protection equipment.  
See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

*Open and handle containers with care.  
Ventilation measures are required in rooms without sufficient air exchange (e.g. closed rooms), because the occupational exposure limit values (see chapter 8) could be exceeded. This must be avoided.  
Wear suitable personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Change contaminated or damaged gloves and contaminated clothing immediately and wash skin immediately. Mix slowly, partially covering the mixing container. Pour carefully and slowly when repotting. Observe the BGBau technical data sheet and practical guide for handling epoxy resins.*

· **Information about protection against explosions and fires:**

*Ensure sufficient air exchange and/or extraction in the working areas. Take precautionary measures to avoid electrostatic discharges.*

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and containers:**

*No special requirements.*

· **Further information about storage conditions:**

*Protect from heat and direct sunlight.*

· **Storage class**

*6.1C*

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Components with critical values that require**

**monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

(Contd. on page 5)

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 4)

· **DNELs**

**CAS: 100-51-6 Benzyl alcohol**

Oral	DNEL	4 mg/kg bw/Tag (ArL) 20 mg/kg bw/Tag (Ark)
Dermal	DNEL	8 mg/kg bw/day (ArL) 40 mg/kg bw/day (Ark)
Inhalative	DNEL	22 mg/m <sup>3</sup> (ArL) 110 mg/m <sup>3</sup> (Ark)

· **PNECs**

**CAS: 100-51-6 Benzyl alcohol**

PNEC	0.527 mg/l (Marine water sediment) 0.1 mg/l (Mew) 1 mg/l (Fresh water sediment)
PNEC	0.456 mg/kg dwt (Bod) 5.27 mg/kg dwt (Fresh water sediment)

· **Additional information:** The lists that were valid during the compilation were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls**

No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures**

Keep away from food, drink and animal feed.  
Remove soiled, soaked clothing immediately.  
Wash hands before breaks and at the end of work.  
Avoid contact with eyes and skin.

· **Breathing equipment:**

If workplace limit values cannot be complied with by ventilation measures or if rooms cannot be technically ventilated, respiratory protection must be worn: Use combination filter A1-P2 (brown/white) in rooms that cannot be ventilated. If oxygen deficiency is expected, use self-contained breathing apparatus. Observe wearing time limits according to §9 (3) GefStoffV in conjunction with BGR 190.

· **Hand protection**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

You can find help with choosing gloves on the website <https://www.bgbau.de/fileadmin/Gisbau/Projekte.pdf>  
For example, we recommend the Sol-vex 37-900 protective gloves from Ansell GmbH. The breakthrough time of the protective gloves can be found under point 8 "Penetration time of the glove material". The selection of a suitable glove depends not only on the material, but also on other quality features and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of glove materials cannot be calculated in advance and must therefore be checked before use.  
Nitrile rubber

(Contd. on page 6)

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 5)

· **Penetration time of glove material**

Recommended material thickness:  $\geq 0.4$  mm

The breakthrough times of the Sol-vex 37-900 protective gloves are around 8 hours.

The following applies to all other gloves:

The exact breakthrough time must be obtained from the protective glove manufacturer and adhered to.

Nitrile rubber

Material thickness:  $\geq 0.40$  mm

Penetration time:  $\geq 480$  min

Butyl rubber:

Material thickness:  $\geq 0.5$  mm

Penetration time:  $\geq 480$  min

· **Eye/face protection**

Tight-fitting safety goggles.

Safety goggles.

· **Body protection:**

Protective clothing

Suitable protective clothing should be worn when working with epoxy resins. In addition to normal work clothing (long trousers, long-sleeved shirt or T-shirt), disposable overalls, aprons, overshoes, sleeve protectors etc. may be necessary depending on the activity. Uncovered areas of skin should be avoided as far as possible, even in hot weather. If the work involves kneeling, the lower leg area should be protected by protective trousers.

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Colour:**

Yellow

· **Smell:**

Characteristic

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

$>200$  °C (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight  $< 700$ )

· **Flash point:**

151 °C

· **Auto-ignition temperature:**

184 °C

· **pH**

Not determined.

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic:**

Not determined.

· **Solubility**

· **Water:**

Not miscible or difficult to mix

· **Steam pressure at 20 °C:**

$<0.1$  hPa (CAS: 25068-38-6 Propyl -2,2-diphenyl-4,4'dipropyloxirane polymers and homologues molecular weight  $< 700$ )

(Contd. on page 7)

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 6)

- |  |                              |
|--|------------------------------|
| · <b>Density and/or relative density</b>   |                              |
| · <b>Density at 20 °C</b>  | 1.14 g/cm <sup>3</sup>       |
| · <b>9.2 Other information</b>   |                              |
| · <b>Appearance:</b>   |                              |
| · <b>Form:</b>   | Fluid                        |
| · <b>Important information on protection of health and environment, and on safety.</b> |                              |
| · <b>Self-inflammability:</b>  | Product is not selfigniting. |
| · <b>Explosive properties:</b>   | Product is not explosive.    |
| · <b>Information with regard to physical hazard classes</b>                            |                              |
| · <b>Explosives</b>  | Void                         |
| · <b>Flammable gases</b>   | Void                         |
| · <b>Aerosols</b>  | Void                         |
| · <b>Oxidising gases</b>   | Void                         |
| · <b>Gases under pressure</b>  | Void                         |
| · <b>Flammable liquids</b>   | Void                         |
| · <b>Flammable solids</b>  | Void                         |
| · <b>Self-reactive substances and mixtures</b>   | Void                         |
| · <b>Pyrophoric liquids</b>  | Void                         |
| · <b>Pyrophoric solids</b>   | Void                         |
| · <b>Self-heating substances and mixtures</b>  | Void                         |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b>     | Void                         |
| · <b>Oxidising liquids</b>   | Void                         |
| · <b>Oxidising solids</b>  | Void                         |
| · <b>Organic peroxides</b>   | Void                         |
| · <b>Corrosive to metals</b>   | Void                         |
| · <b>Desensitised explosives</b>   | Void                         |

### SECTION 10: Stability and reactivity

- |  |   |
|--|---|
| · <b>10.1 Reactivity</b>                                   | No further relevant information available.            |
| · <b>10.2 Chemical stability</b>                           |   |
| · <b>Thermal decomposition / conditions to be avoided:</b> | No decomposition if used according to specifications. |
| · <b>10.3 Possibility of hazardous reactions</b>           | No dangerous reactions known                          |
| · <b>10.4 Conditions to avoid</b>                          | No further relevant information available.            |
| · <b>10.5 Incompatible materials:</b>                      | No further relevant information available.            |
| · <b>10.6 Hazardous decomposition products:</b>            | No dangerous decomposition products known             |

GB

(Contd. on page 8)



## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 7)

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

#### LD/LC50 values that are relevant for classification:

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

Oral	LD50	11400 mg/kg (rat)
Dermal	LD50	23000 mg/kg (rabbit)
		>2000 mg/kg (rat)

CAS: 30583-72-3 Cyclohexanol, 4,4'-(1-Methylethyliden)-, Polymer mit 2-(Chlormethyl)oxiran

Oral	LD50	>5300 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rabbit)

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
	NOAEL 2nd year study	200 mg/kg (mouse)
		200 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4178 mg/l (rat)

CAS: 80-48-8 methyl toluene-4-sulphonate

Oral	LD50	341 mg/kg (rat)
------	------	-----------------

#### Primary irritant effect:

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

#### Respiratory or skin

##### sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### 12.1 Toxicity

#### Aquatic toxicity:

CAS: 1675-54-3 4,4'-Methylenediphenyldiglycidyl ether

LC50/72h	>11 mg/l (algae)
----------	------------------

(Contd. on page 9)



## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 8)

IC50	>42.6 mg/l (Bak)
LC50/96h	2 mg/l (Oncorhynchus mykiss) 1.3 mg/l (fish)
EC50/48h	2.1 mg/l (daphnia) 1.8 mg/l (Daphnia magna)
ErC50/72h	11 mg/l (Selenastrum capricornutum)
<b>CAS: 100-51-6 Benzyl alcohol</b>	
IC50/72h	700 mg/l (algae)
LC50/96h	460 mg/l (Pimephales promelas) 10 mg/l (Lepomis macrochirus)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:** Toxic for aquatic organisms  
Also poisonous for fish and plankton in water bodies.  
Do not allow product to reach ground water, water bodies or sewage system.  
Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

GB

(Contd. on page 10)



BE SURE. BUILD SURE.

Page 10/12

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

Trade name MC-DUR 1204 R - Komponente A

(Contd. of page 9)

### SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name · ADR, IATA · IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin, Ethyl-4-[[[(methylphenylamino)methylen]amino] benzoat), MARINE POLLUTANT
· 14.3 Transport hazard class(es) · ADR · Class · Label	9 (M6) Miscellaneous dangerous substances and articles. 9
· IMDG, IATA · Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA):	Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Kemler Number: · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A, S-F A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information: · ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 (-)

(Contd. on page 11)

GB

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 10)

· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN), 9, III

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes)  
for the application of lower-  
tier requirements**

200 t

· **Qualifying quantity (tonnes)  
for the application of upper-  
tier requirements**

500 t

· **15.2 Chemical safety  
assessment:**

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

(Contd. on page 12)



BE SURE. BUILD SURE.

Page 12/12

## Safety data sheet according to UK REACH

Printing date 12.07.2025

Version number 38 (replaces version 37)

Revision: 12.07.2025

**Trade name MC-DUR 1204 R - Komponente A**

(Contd. of page 11)

H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H360F May damage fertility.  
H361 Suspected of damaging fertility or the unborn child.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data  
specification sheet:**

· **Abbreviations and acronyms:**

Environment protection department.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 1A: Reproductive toxicity – Category 1A

Repr. 2: Reproductive toxicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the  
previous version altered.**

GB